

ABSTRACT										
SR. NO.	DESCRIPTION	UNIT	board room	director's room	faculty room	library	class room	total qty	RATE	AMOUNT
	CHAIRS									
1	FOLDABLE CHAIRS Supplying and fixing chair made from Ghana teak wood frame approx. size 50mmx25mm and 75mm x 25mm in back, cushion in seat and MS powder coated under structure. Seat to be made from geo foam. fabric, rubber. Fabric Basic Rate Rs,350/- Per Mtr. Wood to be finished with malamine polished. Complete as per manufacturer's specification.	NOS.	60	0	0	0	0	60	8,798	527880
2	CHAIRS Supplying and placing the chair with tablet having understructure of MS Frame duly powder coated. The seat to be made of Polypropylene. The back and arm pads to be textured finished in Matte black and made of Polypropylene for ease of cleaning. The frame should have a utility basket mounted below the seat for keeping of miscellaneous material like books. The utility tray should have a facility of being removed when required. The back to have an aperture with soft hand grip for the ease of moving the chair and should provide a firm grip for the movement. The legs to have anti-skid nylon grips. The chair should have the flexibility of joined together when required with the help demountable joineries. The arm rest to have an ABS writing pad for training requirements. The sizes of the chairs to be :- Seat :- 469 (D) X 480 (W) Back :- 490 (W) X 280 (H) Armrest :- 214mm high from the seat.	NOS.	0	0	0	0	200	200	10235	2047000
3	TEACHER'S CHAIR Supplying and erecting fixed chair made from powder coated pipe frame structure with seat and back PU mould, 14 gauge pipe, 25mm dia D type PU frame.	NOS.	0	0	0	0	3	3	6469	19407
4	Fixed chair Supplying and erecting fixed chair made from powder coated pipe frame structure with seat and back PU mould, 14 gauge pipe, 25mm dia D type PU frame.	NOS.	0	0	20	42	0	62	6469	401078
5	LOW BACK CHAIR(VISITOR CHAIR) Supplying and fixing Medium back mesh chair, seat with PU moulded cushion Adjustable armrest with PU pad, gas lift for seat height adjustment, Synchro mechanism with single position back lock, Five prong Nylon base with twin wheel castors.	NOS.	0	3	5	27	0	35	6670	233450
6	HIGH BACK CHAIR (Type 1) Supplying and fixing High back mesh chair with head rest, seat with PU moulded cushion, Adjustable armrest with PU pad, Gas lift for seat height adjustment, Synchro mechanism with single position back lock, Five prong Nylon base with twin wheel castors.	NOS.	0	1	0	1	0	2	14104	28208
	TABLES									
7	TEACHER'S TABLE(1200MM X 600MM) Providing and fixing table with drawer box. Top and verticle support to be made of 25mm th. Prelaminated particle board, and modesty made of 18mm th. Prelaminated particle board. All open edges to be finished with 2mm th. PVC edge band- machine pressed with hot melt glue. 60 mm dia. Wire manager. Drawer pedestal (Movable) with 2 box drawer & 1 file drawer: 400 W x 450 D x 680 mm H. Made of 18 mm th. PLB & compact laminate, metabox channels, anodised finish recessed handles & lock. Complete joinery with KD fittings.	NOS.	0	0	0	0	3	3	20700	62100
8	Corner table-600mmx600mm Providing & fixing centre table and corner table made from 19mm + 6mm marin ply with 1.0 mm thick laminate. Top to be made from 12mm thick clear float glass with bevelled edge. Top to be fixed on leg with limanted panel.	NOS.	2	2	0	4	0	8	6,900	55200
9	Centre table (rectangular 900mm X 450mm) Providing & fixing centre table and corner table made from 19mm + 6mm marin ply with 1.0 mm thick laminate. Top to be made from 12mm thick clear float glass with bevelled edge. Top to be fixed on leg with limanted panel.	NOS.	2	1	0	2	0	5	7,475	37375
10	Reception table with pedestal Providing and fixing reception table made from below specification	Rmt.	0	0	0	2.1	0	2.1	11500	24150

	Entire table and drawer box to be made from 19mm ply with exposed side 1.0mm thick laminate and inner side balancing laminate. Partly 12mm thick bevelled edge glass to be fixed with SS sturd . Partly vertical 12mm thick glass to be provided with SS D bracket.Drawers slid on telescopic chanel. And it should be lockable and SS handle.Complete as per drawing and design.									
11	Librarian table-1800mmx750mm Providing and fixing table with drawer box,side cabinet,key board tray and cpu trolley..Top and verticle support to be made of 25mm th. Prelaminated particle board, and modesty made of 18mm th. Prelaminated particle board. All open edges to be finished with 2mm th. PVC edge band- machine pressed with hot melt glue. 60 mm dia. Wire manager.Drawer pedestal (Movable) with 2 box drawer & 1 file drawer: 400 W x 450 D x 680 mm H. Made of 18 mm th. PLB & compact laminate, metabox channels, anodised finish recessed handles & lock. Complete joinery with KD fittings.Side storage with 2 drawers & swing shutters, size: 900 L x 400 D x 725H. Top made of 25mm thick prelaminate board, Carcass, facia, shutters & shelves made of 18 mm th. PLB. Back made of 3 mm compact laminate. sliding shutter, handles & lock.	NOS.	0	0	0	1	0	1	26238	26238
12	Reading table(1500mm X 1200mm) Providing and fixing reading Table, size: 1500 x 1200 x 750 mm H. made from 25mm th. Prelaminated particle board with 2mm th. hot pressed PVC edge band. Verticle leg and modesty panel to be made from 18 mm th. Both side prelaminate particle board.Complete as per drawing and design.	NOS.	0	0	0	5	0	5	10120	50600
13	Conference table Providing Conference table as per layout: Top made from 36 mm thick MDF board covered with 4 mm th. Veneer, finished with PU coating. Other face is covered with backer lamination. The edges are finished with matching wooden beading. Anodized finish Flip boxes to be provided on top, to facilitate power / data access. A cable tray to be provided below top to pass the cables. Understructure made of pre-laminated boards. Edges to be covered by 2 mm PVC edge bands glued by hot melt glue applied by auto edge banding machine. Joinery to be done using KD system fittings. Shape, shades and accessories to be approved by chief architect before starting the work.	Rmt.	0	0	0	5.4	0	5.4	11500	62100
	Carrels									
14	For four person Library Carrels, 4 person cluster, overall size : 2060 x 2000 ,25mm th. Pre laminated top finished with 2 mm th. hot pressed PVCedge banding (German make). 60 mm dia wire manager. 18mm th. PLB leg supports. .including Parttion, 80 / 30 mm th., 1210 mm high, made of Aluminum alloy frame, Soft board / writing board at upper level & 12 mm th. PLB tiles below. Raceways are provided for concealed cabling of power & data, cutouts for switch sockets as per requirement.	NOS.	0	0	0	3	0	3	63457	190371
15	For two person Library Carrels, 2 person cluster, overall size : 1060 x 2000 ,25mm th. Pre laminated top finished with 2 mm th. hot pressed PVCedge banding (German make). 60 mm dia wire manager. 18mm th. PLB leg supports.including Parttion, 80 / 30 mm th., 1210 mm high, made of Aluminum alloy frame, Soft board / writing board at upper level & 12 mm th. PLB tiles below. Raceways are provided for concealed cabling of power & data, cutouts for switch sockets as per requirement.	NOS.	0	0	0	3	0	3	38468	115404
16	E library 25mm th. Pre laminated top finished with 2 mm th. hot pressed PVC edge banding (German make). 60 mm dia wire manager. 18mm th. PLB leg supports. Drawer pedestal (top supporting) with 1 drawer & 1 cabinet: 300 W x 450 D x 725 mm H. Made of 18 mm th. PLB & compact laminate, metabox Modular Parttion, 80mm th., 725 mm high, made of Aluminum alloy frame, Soft board / writing board at upper level & 12 mm th. PLB tiles below. Raceways are provided for concealed cabling of power & data, cut-outs for switch sockets as per requirement.	Rmt.	0	0	0	12	0	12	11930	143160
17	OFFICE TABLES(2100MM X 750MM)	NOS.	0	1	2	0	0	3	28854	86562

	<p>Providing and fixing table with drawer box,side cabinet,key board tray and cpu trolley.Top and verticle support to be made of 25mm th. Prelaminated particle board, and modesty made of 18mm th. Prelaminated particle board. All open edges to be finished with 2mm th. PVC edge band- machine pressed with hot melt glue. 60 mm dia. Wire manager.Drawer pedestal (Movable) with 2 box drawer & 1 file drawer: 400 W x 450 D x 680 mm H. Made of 18 mm th. PLB & compact laminate, metabox channels, anodised finish recessed handles & lock. Complete joinery with KD fittings.Side storage with 2 drawers & swing shutters, size: 900 L x 400 D x 725H. Top made of 25mm thick prelaminate board, Carcass, facia, shutters & shelves made of 18 mm th. PLB. Back made of 3 mm compact laminate. sliding shutter, handles & lock.</p>									
18	ASST. PROFESSOR'S CABIN(1800MM X 750MM)	NOS.	0	0	3	0	0	3	26238	78714
	<p>Providing and fixing table with drawer box,side cabinet,key board tray and cpu trolley..Top and verticle support to be made of 25mm th. Prelaminated particle board, and modesty made of 18mm th. Prelaminated particle board. All open edges to be finished with 2mm th. PVC edge band- machine pressed with hot melt glue. 60 mm dia. Wire manager.Drawer pedestal (Movable) with 2 box drawer & 1 file drawer: 400 W x 450 D x 680 mm H. Made of 18 mm th. PLB & compact laminate, metabox channels, anodised finish recessed handles & lock. Complete joinery with KD fittings.Side storage with 2 drawers & swing shutters, size: 900 L x 400 D x 725H. Top made of 25mm thick prelaminate board, Carcass, facia, shutters & shelves made of 18 mm th. PLB. Back made of 3 mm compact laminate. sliding shutter, handles & lock.</p>									
19	WORKSTATIONS(Modular)	cluster	0	0	0	0	4	4	70524	282096
	<p>Workstation (4 person cluster), overall size: 3000 x 3000 x 1210H 25mm th. Pre laminated top finished with 2 mm th. hot pressed PVC edge banding (German make). 60 mm dia wire manager. 18mm th. PLB leg supports. Modular Parttion, 80 mm th., 1210 mm high, made of Aluminum alloy frame, Soft board / writing board at upper level & 12 mm th. PLB tiles below. Raceways are provided for concealed cabling of power & data, cutouts for switch sockets as per requirement.Side storage with 2 drawers & 2 sliding shutters, size: 900L x 400D x 750H. Top made of 25mm thick prelaminate board, Carcass, facia, shutters & shelves made of 18 mm th. PLB. Back made of 3 mm compact laminate. allu.sliding chanel, handles & lock.</p>									
	SOFAS									
20	WAITING LOUNGE									
	<p>supply and positioning of synthetic leather fully upolstred sofa made up of polyster fiber wadding 175 GSM(18m) PU foam of 32d,28d,23d in various position.expanded PF sheet for load distribution in seats.durable rubber webbings of 50 mm and 70mm. Cotton webbing on wooden surface to prevent sharp edges.commercial ply 12-15 mm as per design requirement.teak wood of various thickness and length ,duly dried as base structure.all structures are joined with stapling.etc, complete as per manufacturer specification ,detail technical specification,drawings,and as per EIC/architect</p>									
	3S	NOS.	1	1	0	5	0	7	45885	321195
	2S	NOS.	2	2	0	4	0	8	22425	179400
	1S	NOS.	1	0	0	0	0	1	14735	14735
21	CARPET	SQM.	110	0	0	0	0	110	3156	347160

	Providing and Fixing of Bike path(Interface) 475 gsm 100% Solution Dyed quality, level construction tufted loop pile 100% Nylon 6.6 (BCF) recycled carpet tile. Backing glassBac, carpet gauge 1/12" in the size of 25cm X 1mtr Commercial extra Heavy duty carpet tile. Carpet tile is flame resistant ASTM E648 Class 1 with Electrostatic Antistatic properties AAATCC 134<3000 volts. The carpet has to be fixed with Aerobond solution. The measurement will be counted in square meters only and payment will be made on actual quantity installed.Complete with s.s patti on riser									
22	ACOUSTICAL PANELLING	SQM.	90	0	0	0	290	380	5474	2080120
	Providing and supplying Armstrong 'Opra Acoustical Wall Paneling' with square edges made of fibre glass substrate 25mm thick and wrapped on the front side with an acoustically transparent and classified for Fire reaction Class A as per ASTM E-84, fabric with an option of colors – Husk, Copper, Sangria, Sesame, Coffee, Charcoal, Titanium, Flame, Peanut & Shell as per the choice of the Architect of size 600X600 OR 600X1200 mm providing a minimum sound absorption level of 0.85 NRC to be affixed to wall using Wall panel impalers supplied by M/s Armstrong Industries India Pvt. Ltd and construction adhesives as per the instructions laid down by the manufacturer. INSTALLATION: 4nos. Armstrong wall panel Impalers of shall be fixed to the wall surface using self-tapping screws. Silica based construction adhesive to be dabbed on to the projecting elements (spikes) of the impalers. Armstrong Opra wall panels shall be pierced through the spikes of the impalers ensuring the line and level of the panels are maintained. Installation to be carried out by Armstrong Trained Installation team & Installation should be carried out as per Armstrong recommended procedure.									
23	Paneling	sqm	0	0	30	0	0	30	2300	69000
	Providing and fixing paneling on wall and window sill, made from 18mm thick particle board with 1.00 mm thick laminate. Rates are including prepare smooth surface by pop.									
24	Laminated paneling	sqm	0	20	10	100	30	160	5175	828000
	Providing and fixing paneling made from 50mmx25mm hard wood frame with (6+6)mm thick ply with 1.0mm thick laminate with necessary grooves finished with paint.Complete as per instruction given by Architect.									
25	DIAS	SQM.	20	0	0	0	0	20	3,664	73280
	Supplying & fixing of "Kebao" Steel Cement Cavity flooring system (Imported) manufactured by "Kebao Access Floor International Co. Ltd." (Shanghai). Specification of FS800 CL Panel Tile: Size - 600mm x 600mm tile, thickness - 33mm Module - HDG-6008 CL (Bare Finish – Corner lock type) Point Load - 360 Kg. Uniform Dis. Load (UDL) - 1600 Kg. per M 2 Finish : Bare finish with gray colour special weather coating on tile.FFH 175mm. Tile : All steel construction & cavity filled with epoxy mix cement. Pedestal : All steel constructions & Yellow Zinc plated 22mm Dai pipe with bottom plate of 100mm x 100mm x 2mm thick. Top plate of 75mm x 75mm x 3mm thick with threaded bolt & 2 nuts (10mm each) for leveling adjustment & locking. PVC Cap : 75 x 75 x 2mm PVC anti-vibration cap on the top of pedestal Stringer : Stringers of 0.80mm thick rectangular pipe of size – 22mm (W) x 31mm (Ht.) x 573mm long, 2 holes centre to centre 550 mm. Screw : 6mm x 50mm fine thread star screw to fix tile with pedestal. Pedestal Fixing: using epoxy adhesive or with anchor fastener									
26	False flooring	SQM.	55	0	0	0	0	55	4,478	246290

	ARMSTRONG SUSPENSION SYSTEM: Accessories manufactured and supplied by armstrong worlds industries consisting of M6 Anchor Fasteners with Vertical Hangers made of Galvanized steel of size 26X26 X25X1.2 mm with a galvanized of thicknes of 80gsm.A pre-strengthened hanger wire of dia-2.68 mm of 1.83 mm length, thickness of 80 gsm. and a tensile strngth of 344-413 Mpa, along with Adjustable hook clips of 0.8 mm thick , galvanized string steel for 2.68 with a min. pull strength 110 kg.The adjustable clip also consists of a 3.5 m aquiline wire to be used with the main runner.									
38	Removing ang refixing Existing tile base ceiling	SQM.	5	0	0	0	0	5	3450	17250
	Removing existing tile base ceiling for suspended AC open duct from RCC ceiling/beam.And refixed same tiles or new if required tiles with framing.									
39	Cup board with louvers shutter for electrical panel	sqm	0	0	6	6	0	12	8050	96600
	Providing and fixing cup board for electrical panel.entire cabinet to be made from 18mm thick ply with 1.0mm thick laminate.Shutter to be made from 18mm thick ply with s.s. grill. Or teak wood louvers finished with malamine polished. Shutter having a ss lock ,handle and hinges.									
40	Built in storage (veneer finished)	Sq.mt.	20	0	0	0	0	20	9200	184000
	Providing and fixing built in storage made from frame 18mm thick ply with 4.0mm thick veneer on outer side and .6mm thick balancing laminate in internal side.including shelves.Openable shutter should be made from 18mm thick ply with 4mm thick veneer edge and two side 2mm thick pvc edge beading.veneer should be finished with malamine polished. Complete with all fittings and hardware and SS lock,landles and auto closed hinges.Complete as per drawing and design.									
41	Glass partition/partly solid partition	Sq.mt.	0	12	125	60	0	197	10350	2038950
	Providing and fixing fully glazed partition using 12mm thk toughened glass upto APPROX. 2400mm/2500mm height from floor lvl. Modi guard make clear toughened float glass fixed with necessary patch fittings(Archie/Ozone/ENOX make), D brackets etcincluding top, bottom allu. sleek chanel.and partly double skinn laminated partition.nade from 50mm x 37mm hardwood frame clad with 9mm thick ply with 1.0mm thick laminate.open edges also finished with ply and laminate. As per the manufacturers specification or as directed by the Architect.									
42	Glass door	Sq.mt.	0	2	4	4	0	10	11500	115000
	Providing and fixing glass door with patch fitting as shown in the drg. Door shall consist of approved make 12mm thk. toughened clear float glass with pre-fitted necessary hardwares of Enox / Ozone make for smooth swinging action. Rate shall include necessary approved locking systems, S.S. brush finished 'H' type Handle pair, floor springs (Heavy duty or equivalent), gaskets & miscellaneous hardware items. Including all materials and labour etc. complete as per detail drawing and instruction of engineer-in charge and consultant. Drg.no.-06									
43	Glass railing	Rmt	0	0	0	50	0	50	19550	977500
	Providing & fixing modular type staircase railing with Floor fixed balustrade system at staircase of AISI 304 satin polished steel 54x12mm solid bar uprights at maximum c/c distance of 1500 mm fixed in RCC with 77 x 140 mm core dia & filled with epoxy grout. Handrail should be of 38 mm dia x 1.5 mm thk fit to site at maximum railing height of 1000 mm from FFL respectively at staircase. Handrail supported by bead blasted unified stem keys and fixation adjusted to be plumb and in-line with all other balustrade posts having 12mm thk clear toughened Glass (Siant Gobian/ Ashahi) as infill, supported on upright with through-hole fixation, etc complete with all necessary bends & terminations etc,complete as per the detail technical specifications and drawings, entire work should be carried out by the manufacturures approved persons only.(Approved makes for railing are Q- railing/ Kitch/ Jindal).(Only Length will be paid for payment). The Work to be executed as per consultant drawing .									
44	Glass shelves 400mm to 300mm depth	Sq.mt.	0	1	1	0	10	12	3450	41400
	Providing and fixing 12mm thick float glass with bevelled edge for shelves. Fixed with SS D bracket with wall/paneling									
45	Middle ht. partition	sgm	0	0	30	0	0	30	6049	181470

	Modular Partition, 80 mm th., 1210 mm high. Made of Aluminum alloy frame, Soft board / writing board at upper level & 12 mm th. PLB tiles below. Raceways are provided for concealed cabling of power & data, cut-outs for switch sockets as per requirement.									
46	PIN BOARDS	sqm	0	0	30	10	5	45	3680	165600
	Providing and fixing pinup boards. It consist 12mm soft boards of good density to be mounted over 12mm ply. The soft board will be covered with a plain fabric (approx Rs.150 /Rmts.) from front and edges. Suitable moulding (as directed by architect) will be fixed on all four sides and will be finished in polish.									
47	Notice board (Size:1800 x1200)	Sq.mt.	0	0	0	1	2	3	3680	11040
	Providing and fixing pinup boards. It consist 12mm soft boards of good density to be mounted over 12mm ply. The soft board will be covered with a plain fabric (approx Rs.150 /Rmts.) from front and edges. Suitable moulding (as directed by architect) will be fixed on all four sides and will be finished in polish.									
48	Notice board with shutter (Size:1800 x1200)	NOS.	0	0	0	1	1	2	4600	9200
	Supplying and fixing notice board with : (A) Cloth: Woolen Fabric; Colour : maroon/Green/Violet. Thickness: 1±0.1 mm. The top surface should be smooth, finish, un-stretchable, fungus proof, terminate proof & eye catching. The color should not be dull in Direct sunlight position. (B) Laminated Sheet: Back Side: The Backside of the board covered with 1±0.1 mm laminated surface. Paper Laminated Sheet will not be allowed (C) Soft Board: Thickness: 11.00 mm. Density should be 2.5 kg/m2. Linear expansion/ contraction in range 33% to 90% RH @ 200 C: % max. 0.5. The core material is soft board. So, it should be of standard company make with good quality & density. The board should be soft, resilient, light colored sheet material. (D) Cover: The Acrylic Cover Of The Notice board should be framed with anodized aluminium round framing with given specification. The Acrylic Should be Imported Clear Resin Acrylic With Thickness of 2 mm. The acrylic should be clear, transparent, & not dull in direct sunlight position. The Cover should be fixed with the soft board with stainless steel hinges & provided With Locking facility. (E) Aluminum Frame: The Frame Section Shall Be front: 20 mm, Side : 16 mm, Wall Thickness : 1.2 mm shall be Coated with silver matt Anodise of 10 Micron (+/- 2 micron) (F) Corner: ABS plastic With Chrome Plating Match With									
49	BLACKBOARDS	NOS.	0	0	0	0	3	3	19665	58995
	Providing and fixing 1200mmx3600mm white back laminated 12mm tk glass with fixing 17 gauge MS plate of size 150mm x 900 mm, finished with matt/brush silver powder coating on right side of the glass white board and fitting to the partition with 25mm dia SS studs as per drawings and approvals including magnetic duster, magnets, markers etc. complete.									
50	Curtain									
	Sunscreen	sqm	0	3	27	140	0	170	3156	536520
	Providing and fixing Translucent Roller Blind fixed on window level on wooden batten and curtain lift with cotton thin rope, design and colour as per instruction by engineer – in – Charge with necessary hardware fitting, material and labour etc. complete as per detail drawing and instruction of engineer-in charge and consultant. Approved make Vista / Neon or equivalent.									
51	Frost Decorative Film on Glass	Sqmt.	20	10	50	60	0	140	1150	161000
	Providing and fixing on vertical mount Glass substrate approved frosted decorative film avg. 15 micron thick of approved make pasted on one side only with standard installation practice as provided by the manufacturer , as per detailed design drawing.Item to include all cutting to form design pattern, all accessories, men material and lift up to 5 mts., cleaned complete. Item to be completed in all respects as per drawings & instructions from Project-in-charge/Architect.									
52	Protective sheet on floor	Sq.mt.	200	20	60	700	200	1180	138	162840

	Supplying & laying of floor protection sheet on flooring of size 1800mm X 1200mm X 2mm thick, adhesive tap shall be fixed between two sheet, as per the instruction of EIC/Architects. Contractor has to remove the same after completion of work/hand over the site. Cost is inclusive of all the connected works from supply, laying to removing, cleaning, disposing debris to an unobjectionable place, etc.									
53	black out (Roll up blinds) Providing and fixing Black out Roller Blind fixed on window level on wooden batten and curtain lift with cotton thin rope, design and colour as per instruction by engineer – in – Charge with necessary hardware fitting, material and labour etc. complete as per detail drawing and instruction of engineer-in charge and consultant. Approved make Vista / Hunter Douglas / Neon or equivalent.	Sq.mt.	0	0	0	40	0	40	2990	119600
54	TRAPE DOOR at 6mt ht. Providing and fixing trape door made from 12mm thick BWP ply with 1.0mm thick laminate and teak wood beading, door to be suspended from RCC ceiling/beam from Ghana teak frame or MS angle, door to be complete with ss hinge and lock.	Sq.mt.	0	0	0	16	0	16	2990	47840
55	BRICK WALL(Full Brick) Brick work using common burnt clay building bricks having crushing strength not less than 35kg/Sqcm. In foundation and plinth. In cement mortar 1:5(1cement:5fine sand) (A) Modular	CU.M.	5	5	10	5	30	55	3206	176330
56	BRICK WALL(Half Brick) Half brick masonry in common burnt clay-building bricks having crushing strength not less than 35kg/cm2 in cement mortar 1:4 (1 cement : 4 coarse sand) (A) Modular	SQM.	15	10	25	30	180	260	457	118820
57	Providing 15mm thick cement plaster in single coat on brick/ concrete walls or interior plastering for clear height from floor to floor level of max 4.65m and work should be carried out for any floor level at any height finished even and smooth in 1:6 (1 cement: 6 fine sand)	SQM.	20	30	60	50	400	560	161	90160
58	Painting two coats (including priming coat) over new wood and wood based surfaces with ready mixed paint, interior to give even shade including cleaning oil, grease, dirt and other foreign matter, sand papering & stopping.	SQM.	40	40	80	100	400	660	253	166980
59	Providing and fixing flush door shutters solid core construction with frame of first class hardwood with cross band and face veneer or plywood face panels including anodized aluminium but things with necessary screws, (B) Non-decorative type & blockboard core anodized aluminium but things in flush door shutters 35mm thick	SQM.	0	0	0	0	25	25	7475	186875
60	Remove the existing door carefully so as not to damage structural components and handing over the same to the client in a neat, stacked member, also, making good & any damage incurred in the process the rate shall be in sqm bases.	SQM.	0	0	0	15	0	15	115	1725
61	Dismantalling of R.C.C work : Demolition and disposal of unserviceable materials with all leads and lift for R.C.C works Rate also including necessary tools scaffolding and all safety measures required for the same, including all leads and lifts.	cmt	0	0	0	10	0	10	473	4730
62	Dismantalling the existing Railing carefully so as not to damage structural components and handing over the same to the client in a neat, stacked member, also, making good & any damage incurred in the process the rate shall be in Rmt bases.	Rmt	0	0	0	50	0	50	805	40250
	Metalic paint	Sq.mt.	20	10	20	60	20	130	500	65000
	Supplying and applying approved make metallic paint on AC G I duct.									
									Grand total	18570678